



STANDFIELD VIDEO SERVICES LLC



+1 (833) 318-3680

+1 (614) 578-8420

[HTTPS://STANDFIELDVIDEO.COM](https://standfieldvideo.com)

BENJAMIN@STANDFIELDVIDEO.COM

ADMIN@STANDFIELDVIDEO.COM

SVS ATEM Constellation Package SPEC SHEET

Engineering Case

Main Use: Switcher, tally, genlock, network, MV conversion.

RU1: ATEM 2ME Constellation

- 2 Mix Effects, 2 DVEs, 20 Inputs, 12 Outputs, L&R XLR/TRS Inputs, Thunderbolt Program Output, 2 Multiviews (16 sources each)
- Maximum Resolution 3G 1080P@59.94

RU2: Engineering Peripherals Tray


- Tally System with harness attachment on the rack.
 - The tally harness can be configured for 8 separate sources for any pin-out using Canford Audio push-button wiring.
- Programmable Genlock
- Two Video Converters for Multiview
 - This makes both HDMI and SDI outputs available for both multiviews.
- 1GB Ethernet switch



RU3: Furman Power Conditioner

RU4: Cable Management / D-Sub-25 for Tally

- Ports:
- (4x) Genlock Outputs
 - (1x) Dual USB for switcher/peripheral control.
 - (1x) Cat5 Talkback for Blackmagic Camera Comm
 - (1x) Multiview 1 - SDI Output
 - (1x) Multiview 1 - HDMI Output
 - (1x) Multiview 2 - SDI Output
 - (1x) Multiview 2 - HDMI Output
 - (3x) Cat5 Ethernet ports
 - (1x) Audio Left Input (XLR/TRS)
 - (1x) Audio Right Input (XLR/TRS)



- Features:
- 4RU rack inside a shippable/flyable case.
 - Every SDI Output contains both timecode and embedded audio.
 - Thunderbolt Program Output
 - Shipped along with (2x) Laird 16-Pair SDI Harnesses for easy patching between racks.

- In The Case:
- (1x) 4RU Rack
 - (1x) Tally Harness Breakout
 - (8x) Canford Audio Male XLR Push-Button Wiring
 - (8x) Female XLR Turn-Arounds
 - (1x) BNC Tool
 - (1x) System/Network sheet.



Ship Weight: 50LBS. *May change based on shipping needs.

Ship Dimensions: 25IN x 16IN x 15IN

Router Case

Main Use: The SDI Router provides powerful flexibility with the Constellation Switcher

RU1&2: 12G 40x40 SDI Router

- Resolutions up to true 4K (4096x2160@60)

RU3: Furman Power Conditioner

- Features:
- 3RU rack inside a shippable/flyable case.
 - Shipped along with (2x) Laird 16-Pair SDI Harnesses for easy patching between racks.
 - Genlockable
 - Network Control

- In The Case:
- (1x) 3RU Rack
 - (1x) BNC Tool

Ship Weight: 35 LBS. *May change based on shipping needs.

Ship Dimensions: 22IN x 15IN x 13IN



Panel Case


Main Use: Video Switcher Panel, Conversion

Custom Case: ATEM Advanced 20 Button Panel

- Capable of controlling 4ME ATEM Switchers of any resolution.
- Thunderbolt Control
- (4x) Ethernet ports act as a switch.

Conversion: (15x) Blackmagic Bi-Directional 3G SDI HDMI Converters

- Capable of converting 30 signals simultaneously.
- (15x) Regular Transformer Power Supplies
- (15x) USB-C to USB-A 3.0 - 6' cables
 - Ability to alternately power the device.
 - Device control
 - All converters set to 3G-Level A



Laptop: (1x) ASUS Laptop

- Capable of controlling Switcher/Panel/Tally/Conversion/Router
- Come with the following:
 - (1x) Power supply
 - (1x) Lock
 - (1x) Ethernet NIC / USB Hub
 - (1x) 6' USB 3.0 to USB 3.0 Cable
 - (1x) 6' Thunderbolt4 Cable
 - (5x) 10' Ethernet Cables

Features: Shippable/flyable custom case.

Ship Weight: 80 LBS. *May change based on shipping needs.

Ship Dimensions: 34IN x 24IN x 15IN



Monitor Bridge

- (2x) 28" Monitors available for Florida shows at no extra charge.



*Banana for scale